

TOTAL

Sicherheit und Feuerschutz

M6L Wet Chemical Stored Pressure Fire Extinguisher



Application and use:

The TOTAL 6ltr wet chemical fire extinguisher is designed for use against F class cooking oil and fat fires. Primary uses would be in the catering industry such as canteens, hotels, fast food outlets and industrial food production. Additional uses include protection for households, laboratories, workshops, offices, shops, garages and industrial plants. The extinguisher also offers combat against A class fires

Key product features:

- ✓ Swirl-effect, multi-spray nozzle for optimal droplet dimension and projection range
- ✓ Suitable against cooking oil and fat fires F class extinguisher according to newest version of EN3-7
- ✓ Internal corrosion protected with 1mm coating
- ✓ Safe for inadvertent use on electrical equipment (up to 1000v at 1m distance)
- ✓ Pressure gauge with permanent pressure control
- ✓ A test valve is located behind the pressure gauge, ensuring a leak free seal and ease of maintenance
- ✓ High corrosion protection for entire unit, inside and out
- ✓ Cadmium and TGIC-free polyester powder coating
- ✓ Each cylinder is inspected using high-voltage test equipment at the initial coating stage and at the final production process
- ✓ Rubber padded wall bracket protects coating
- ✓ Large diameter neck ring for easier service inspection
- ✓ Container with external thread for protection of anti-corrosive coating, even in the threaded area
- ✓ Added purification tablet means no contamination issues

Approvals:

- ✓ Approved to BS EN 3 (Kitemark)
- ✓ CE marked scoring to PED 97/23/EG
- ✓ Manufacturer is ISO 9001 : 2000 certified by Tuv CERT
- ✓ Cylinder and entire extinguisher tested to European PED
- ✓ Cylinder 100% pressure tested
- ✓ Extinguisher, valve and hose corrosion tested to ISO 3768
- ✓ Each cylinder is inspected using high-voltage test equipment at the initial coating stage and at the final production process
- ✓ Suppression agent tested and certified by European toxicological and hygiene safety Notified Body

Technical specification:

Capacity	Cylinder	Type	Temp. Range	Rating	Weight	Width	Height
6ltr	Steel	Stored Pressure	5°C to 60°C	13A/75F	11.00kg	225mm	560mm

